



Keyboard

By Mary L Devendorf

All seam allowances should be a scant $\frac{1}{4}$ ".
Adjust seam allowances if necessary.

- (2) $2\frac{1}{2}$ " x $1\frac{1}{2}$ " Background Fabric
- (2) $1\frac{1}{2}$ " x $1\frac{1}{2}$ " Background Fabric
- (1) $15\frac{1}{2}$ " x $1\frac{1}{2}$ " Background Fabric

- (1) $12\frac{1}{2}$ " x $1\frac{1}{2}$ " Black Keyboard Fabric

1. Place (2) $1\frac{1}{2}$ " Background squares, right sides together on both ends of $12\frac{1}{2}$ " x $1\frac{1}{2}$ " Black Keyboard rectangle.
Sew on diagonal.
Trim away excess fabric



2. Press triangle toward outside.

When complete Unit 1 should measure $12\frac{1}{2}$ " x $1\frac{1}{2}$ ".

UNIT 1

3. Sew a 2 " x $1\frac{1}{2}$ " Background rectangle on either end of Black Keyboard.



4. Press seams toward Background.

When complete Unit 2 should measure $15\frac{1}{2}$ " x $1\frac{1}{2}$ ".



UNIT 2

6. Sew a $15\frac{1}{2}$ " x $1\frac{1}{2}$ " Background rectangle to top edge of Keyboard.



7. Press seams toward outside.

When complete Block should measure $15\frac{1}{2}$ " x $2\frac{1}{2}$ ".



UNIT 5